

HV-6216V

16CH H.264 Stand-Alone Network DVR



Features

- ◆ Adopts the standard Main profile H.264 compression technology, supports 16ch recording, network transmission, and playback simultaneously
- ◆ Support dual-stream transmission for all channels
- ◆ Support Multiplex operation: live, record, playback, backup, network transmission, mobile phone surveillance
- ◆ Support backup with USB Flash Disk, Movable hard disk, USB writer, Network
- ◆ Support 1channel main output, 1channel SPOT output, 1channel VGA output
- ◆ Support password watermark function to avoid data modification
- ◆ Support Email alarm
- ◆ Support PTZ preset and Cruise Control
- ◆ Mobile phone surveillance (Win CE/Symbain/iPhone/Blackberry)
- ◆ Support Multi-language OSD
- ◆ Support mouse, remoter controller, panel operating

Specifications

Model Name	HV-6216V
Operating System	Embedded Linux OS
Video Compression Format	Main Profile H.264
Video Input	16 Channels BNC
Video Output	1channel BNC,1channel SPOT,1channel VGA(1280*1024)
Audio Input/Output	4 channels RCA/1channel RCA
Display Picture	1/4/8/16
Multiplex Operation	Live\display\Playback\Recording\Backup\ Mobile phone Surveillance \Network simultaneously
Display Resolution	PAL:D1(704*576),NTSC:D1 (704*480)
Recording Mode	Manual\Timer\Motion Detection\Alarm
Recording Frame Rate	D1@100fps,HD1@200fps,CIF@400fps adjustable
Recording Quality	Single channel adjustable
Recording Resolution	PAL:D1(704*576),HD1(704*288),CIF(352*288), NTSC:D1(704*480),HD1(704*240),CIF(352*240)
Recording Playback	1ch、4ch、8ch、16ch simultaneously(playback channel option)
Recording Backup	USB、Moved Hard Disk、USB Writer、Network
Network Transmission	16 Channels real-time Network transmission with QCIF resolution
Recording Play	Special player, Support AVI file format conversion
SPOT Alarm Pop	Support
Alarm Input/Output	16 channels input /4 channels output
Action with Alarm	Support
Email Alarm	Send pieces to the designated email
PTZ	Supports PTZ preset (PELCO-D,PELCO-P)
HDD	2 SATA(one per 2T storage)
Network and Protocol	1 RJ-45 10/100M via Ethernet, Support TCP/IP、PPPOE、DHCP、DNS、 DDNS、NTP、UPNP
IE Browser	Support
Client Software	Support
Dual Stream	Support (Main and secondary interchange)
Group play	Max Support five users online access
Watermark	Support
Multi-language	Support
Mobile Phone Surveillance	Support Windows\ Symbian\ iPhone\Blackberry Operation System
Mouse Interface	USB2.0
Backup interface	USB2.0
Remote Controller	Support
DST	Support
Power	DC12V/6A
Working Temperature	0°C-50°C
Working Humidity	10%—90%
Dimension	430*345*66mm(L*D*H)

Design and specifications are subject to change without notice.